

Adaptive Desk

Adaptive Desk

R240, R250 Product Manual



Contents

Important information	3
Safety messages	4
Recommended use and item dimensions	5
Check your order	6
Basic item	6
Accessories	6
Tilt adjustment	6
Raised edge	6
Elbow supports	7
Adjustable cutout	7
Casters	7
Stationary feet	7
Anti-tip rollers	8
Side storage box	8
Device mount clamp adapter	8
Slide-on ledge	8
Magnet-ready desk surface	9
Flexible dry-erase sheet	9
Multifunction magnetic ledge	9
Operation	10
Maintenance, cleaning and warranty	10
Materials and user modifications	11

IMPORTANT

Please save this product manual for future reference. Additional copies are available at www.rifton.com

Key for users

Use this key to determine which sections of this product manual apply to you.

 **Technical Users** For professionals who order and set up Rifton products.

 **Home Users** For care-givers who use Rifton products on a regular basis.

 **Maintenance Personnel** For anyone who is responsible for service or re-ordering of Rifton products and parts.

WARNING



- Thoroughly read and understand the information in this product manual before attempting to use this product. If the procedures and instructions in this product manual are not followed, serious injury or death could occur.
- A qualified professional must assess the appropriateness and safety of all equipment for each user.
- This product is intended for use by clients of unreliable judgment. Adult supervision is required at all times.
- To prevent falls, strangulation, head entrapment or other injuries:
 - Do not allow users to climb on desk.
 - Ensure user's arms and feet are clear of frame when adjusting height.
 - Do not adjust desk under load.
- To prevent structural failure, which may result in serious injury or death:
 - Inspect this product and accessories regularly for loose or missing screws, metal fatigue, cracks, broken welds, missing attachments, general instability or other signs of excessive wear.
 - Immediately remove this product from use when any condition develops that might make operation unsafe.
 - Do not use Rifton components or products for any purpose other than their intended use.

Recommended use

The Rifton Adaptive Desk can be used to provide a surface for educational and creativity purposes for individuals who benefit from easy height and/or tilt adjustment of a desk to meet their needs. The size and shape of the desk frame and the positioning of the controls are also ideal for assisting wheelchair or activity chair users who require access to a desk surface for their work or activities.

User and item dimensions

Key dimensions – inches (cm)	R240	R250
Surface width	32 (81)	40 (102)
Surface depth	24 (61)	24 (61)
Overall depth	26 (66)	28 (71)
Frame inside width	25½ (65)	33½ (85)
Item weight – lb (kg)	62 (28)	68 (31)
Height range	23–43 (58 – 109)	23–43 (58 – 109)
Tilt range	0°–50°	0°–50°
Elbow support size	4½ x 8½ (11 x 22)	4½ x 8½ (11 x 22)
Adjustable cutout range	10–12 (25 – 30)	10–19 (25 – 48)

Check your order

If your shipment is incomplete or in any way damaged on arrival, please call Customer Service, 800.571.8198.

Basic item

Height adjustment

CAUTION

To avoid crushing or pinching, ensure user's arms and feet are clear of desk frame before adjusting height. Do not adjust under load.

Figure 6a: To adjust the height of the desk, depress the foot pedal (A) and lift or lower the desk to the desired height before releasing the pedal.




Figure 6a

Accessories

Tilt adjustment

Figure 6b: To adjust the desk surface tilt angle, depress the hand lever (B) on the front corner and lift or lower the desk surface to the desired angle.




Figure 6b

Raised edge

Figure 6c: The raised edge adds a 1/4" high boundary to the perimeter of the desk surface to help prevent objects from rolling or sliding off. The raised edge has gaps for the user's elbows and space on the corners for sliding on edge-mounted accessories (see page 8).




Figure 6c

Elbow supports

Figure 7a: To attach to the desk, insert knobs (A) through the elbow supports into the threaded holes in the underside of the desk surface along the user edge. Tighten knobs securely.

Adjustable cutout

Figure 7b: The elbow supports can be attached in a narrow or wide position to create a cutout that can be adjusted 10"–12" (25 – 30 cm) for the R240, and 10"–19" (25 – 48 cm) for the R250.

Casters

Figure 7c: Casters allow mobility of the Adaptive Desk and can lock to provide a stable base.

Stationary feet

Figure 7d: Stationary feet provide a high-friction, stable support base to the Adaptive Desk.



Figure 7a



Figure 7b



Figure 7c



Figure 7d

Anti-tip rollers

Figure 8a: To install the anti-tip rollers, slide the plastic bracket (A) over the front of the lower frame tube, swing the knob (B) into place and tighten securely.

Side storage box

Figure 8b: To install the side storage box, slide it over the right side, lower upright, and rotate the locking lever (C) to secure it in place.

Device mount clamp adapter

Figure 8c: Only necessary on desk surfaces with raised edges, this adapter provides a sturdy location to affix a table edge clamp for a device holder.

Slide-on ledge

Figure 8d: Push the ledge onto the user-facing edge of the desk to one side of center and slide it into place at the center as shown (D).




Figure 8a



Figure 8b



Figure 8c



Figure 8d

Magnet-ready desk surface

Figure 9a: The magnet-ready desk surfaces have a steel underlayerment for attaching magnetic accessories.

Flexible dry-erase sheet

Figure 9b: The flexible dry-erase sheet can be rolled out on the magnet-ready desk surface for creative writing and drawing with dry-erase markers.

Multifunction magnetic ledge

Figure 9c, 9d and 9e: Use this magnetic accessory as a paper hold-down, ruler, straight-edge, or tablet and communication device ledge.



Figure 9a



Figure 9b



Figure 9c



Figure 9d



Figure 9e

Operation

Adjust the height and tilt of the desk to allow an ergonomic position for the user, whether seated or standing. Lock casters before use.

Maintenance

This product is designed and tested for an expected life of twelve years when used and maintained in accordance with this manual. At all times, clients must ensure that the product remains in a safe and usable condition, including regular maintenance and inspections as specified in this product manual.

To prevent structural failure, which may result in serious injury or death:

- Inspect this product and accessories regularly for loose or missing screws, metal fatigue, cracks, broken welds, missing attachments, general instability or other signs of excessive wear.
- Immediately remove this product from use when any condition develops that might make operation unsafe.
- Do not use Rifton components or products for any purpose other than their intended use.
- Replace or repair components or products that are damaged or appear to be unstable.
- Use only Rifton authorized replacement parts. Order information for replacement parts is provided on the back of this product manual.

Cleaning

Clean with disinfectant wipes or a solution of up to 10% bleach. Do not use excessive amounts of water, especially on the desk surface.

Warranty Statement

If a Rifton product breaks or fails in service during the first year, we will replace it free of charge.

Materials 🛠

- Steel hardware items (nuts, bolts, screws, etc.) are typically zinc or nickel plated, or stainless steel.
- Frames are typically steel or aluminum tubing, welded together, and coated with a baked-on paint finish. Some frame components may also be stainless steel.
- Plastic components are typically injection molded from a variety of industrial resins.

All materials are latex, lead and phthalates free.

User modifications 🧑🏠🛠

⚠ WARNING To prevent serious injury or death, do not modify or alter Rifton products or components, or use Rifton products or components in conjunction with products from other manufacturers. Rifton does not accept responsibility for any modifications or alterations made to our components or products after they leave our premises. Customers modifying or altering our components or products, or using them in conjunction with products from other manufacturers, do so at their own risk.

Rifton Contact Information



Email

Sales@Rifton.com



Phone

800.571.8198
9–5 EST



Mail

Rifton Equipment
PO Box 260
Rifton NY 12471–0260



Fax

800.865.4674



Online

www.Rifton.com

To order replacement parts

1. **Locate the ID number** of the product on the small white label.
2. Have this number available when you call **800.571.8198** for your customer service representative.

Use only replacement parts supplied by Rifton Equipment.

We are glad to supply replacement parts throughout the 12 year expected life of the product. Although Rifton makes every effort to supply correct parts and instructions for repairing or refurbishing your equipment, you are responsible to make sure that the repairs or modifications are correctly and safely completed.



See our website for more product information and pricing:
www.rifton.com/desk